



**MODEL: HAULER 1200**  
**TYPE: GASOLINE POWERED TRUCK**  
**MODEL YEAR: 2012**  
**Part No.: 618843**



**PRODUCT SPECIFICATION**

**CONFIGURATION HIGHLIGHTS**

Engine: 13.5 hp (10.1 kW) Exceeds SAE J1940 Standard, 4 cycle, 24.5 ci (401 cc) single cylinder, air-cooled by Kawasaki  
 Valve Train: Overhead valve Fuel System: Fixed float bowl with remote pulse fuel pump  
 Lubrication Pressurized oil system, spin-on oil filter Ignition: Electronic spark/magneto  
 Balancer: Internal counter rotating balance shaft Air Cleaner: Replaceable dry cartridge  
 Electrical: Starter/Generator, solid-state regulator, 12 Volt maintenance free battery (425 CCA, 60 minute reserve)  
 Drive Train: Automatic, continuously variable transmission (CVT)  
 Brakes: Dual rear wheel mechanical self-adjusting drum brakes. Automatic single point park brake release with self-compensating system  
 Transaxle: Differential with helical gears, ground speed governor, forward/reverse  
 Cargo Bed: Roto-molded cross-linked polyethelene. Lifts for access to powertrain. Removable hinged multi-position tailgate requires no latch

**PRODUCT OVERVIEW**

Dimensions		Performance	
Overall Length	113 in (287 cm)	Seating Capacity	2 Persons
Overall Width	49.5 in (128 cm)	Dry Weight	938 lb (425 kg)
Overall Height (No Canopy)	46.5 in (118 cm) (Top of steering wheel)	Curb Weight	978 lb (443 kg)
Overall Height (With Canopy)	70.0 in (178 cm)	Bed Load Capacity	800 lb (365 kg)
Wheel Base	77.0 in (196 cm)	Vehicle Load Capacity	1200 lb (545 kg)
Front Wheel Track	37.0 in (94 cm)	Outside Clearance Circle	22.0 ft (6.7 m)
Rear Wheel Track	38.0 in (97 cm)	Intersecting Aisle Clearance	N/A
Gnd Clearance @ Differential	4.3 in (11 cm)	Speed (Level Ground)	Fwd - 16.5 mph ± 0.5 mph (25.7 kph ± 0.8 kph) Rev - 11.6 mph ± 0.5 mph (18.6 kph ± 0.8 kph)
Cargo Box Width (inside)	44.0 in (112 cm)	Towing Capacity	720 lb (360 kg) max load
Cargo Box Length (inside)	36.0 in (91 cm)	<b>Steering &amp; Suspension</b>	
Cargo Box Depth (inside)	10.5 in (27 cm)	Steering	Self-compensating rack and pinion
Cargo Box Capacity	9.6 cu ft (0.27 m3)	Front Suspension	Leaf springs with hydraulic shock absorbers
Cargo Box material	Roto-molded polyethylene	Rear Suspension	Leaf springs with hydraulic shock absorbers
<b>Vehicle Power</b>		Service Brake	Rear wheel mechanical self-adjusting drum
Power Source	4 Cycle 24.5 cu in (401 c)	Parking Brake	Self-compensating, single point engagement
Valve Train	Single Cylinder OHV	Front Tires	Links 18 x 8.50 - 8 (4 Ply Rated)
Horsepower (kW)	13.5 hp (10.1 kW) Exceeds SAE J1940 Std.	Rear Tires	Turf Saver 18 x 8.50 - 8 (Load Range B)
Electrical System	Starter/Generator. Solid State Regulator	<b>Body &amp; Chassis</b>	
Batteries (Qty, Type)	One, 12 Volt Maintenance F	Frame	Welded steel with DuraShield™ powder coat
Key or Pedal Start	Pedal	Front Body & Finish	Injection Molded TPO
Air Cleaner	Replaceable Dry Cartridge	Rear Body & Finish	Steel. Base coat/clear cc
Lubrication	Pressurized Oil System	Standard Color	Hunter Green
Oil Filte	Spin-On		
Cooling System	Air Cooled		
Fuel Capacity	5.8 Gallon (22.0 L) tank		
Drive Train	Continuously variable transmission (CVT)		
Transaxle	Differential with helical gears		
Gear Selection	Forward - Reverse		
Rear Axle Ratio	11.42:1 (Forward) 15.78:1 (Reverse)		



Some items shown may be optional equipment



CUSHMAN

**OPTIONS & FIELD INSTALLED ACCESSORIES (Installation not included)\***

Item	Std	Opt	Fld	Item	Std	Opt	Fld
<b>TIRES &amp; WHEELS:</b>				<b>ELECTRICAL:</b>			
<b>Front:</b>				<b>Battery Charger</b>			
Links 18 x 8.50 - 8 (4 Ply Rated)				48 VDC Delta Q, 120/230 VAC 50/60 Hz w/18' DC Cord			
USA Trail 18 x 8.50 - 8 (Load Range C)				48 VDC - SCR			
Turf Saver 18 x 8.50 - 8 (Load Range B)				48 VDC - 230 VAC 60 Hz		<input checked="" type="checkbox"/>	
<b>Rear:</b>				48 VDC - 120 VAC 60 Hz			
Links 18 x 8.50 - 8 (4 Ply Rated)				Battery Charger Delete			
USA Trail 18 x 8.50 - 8 (Load Range C)				<b>Other:</b>			
Turf Saver 18 x 8.50 - 8 (Load Range B)				Unique Individual Key Switch			
<b>Wheel Covers:</b>				Headlights			
Spoke, Black & Gold					<input checked="" type="checkbox"/>		
Spoke, Black & Silver				Headlights & Taillight			
<b>COLORS:</b>				Brake Light:			
Body Color - Hunter Gre				Turn Signals with 4-Way Flashers			
Body Color - Ivory				Strobe Light			
Body Color - Bright White				Work Lights			
Body Color - Yellow						<input checked="" type="checkbox"/>	
Body Color - Orange				Work Lights with Strobe Light			
Custom Body Color						<input checked="" type="checkbox"/>	
Seat Color - Tan				<b>Miscellaneous:</b>			
Seat Color - Oyster				DC Converter			
Seat Color - Gray						<input checked="" type="checkbox"/>	
Seat Color - White				Non Standard Battery Option			
<b>HAULING &amp; TOWING:</b>				Hour Meter			
2 in (5 cm) Receiver (Rear)						<input checked="" type="checkbox"/>	
1 7/8 in (48 mm) Ball (Rcvr Req'd)				<b>WEATHER PROTECTION:</b>			
Angle (Rcvr Req'd)				Sun Canopy (Top) Black			
Clevis (Rcvr Req'd)							<input checked="" type="checkbox"/>
Angle, Drop (Rcvr Req'd)				Windshield Fold Do			
1 7/8 in (48 mm) Ball, Drop (Rcvr Req'd)							<input checked="" type="checkbox"/>
Clevis, Drop (Rcvr Req'd)				Weather Enclosure (3 Side, Top & Windshield Req'd)			
Power Dump (Electric)							<input checked="" type="checkbox"/>
Trailer, Dump (Steel Bed)				Windshield Flat			
Trailer, Dump (Poly Bed)							<input checked="" type="checkbox"/>
Aluminum Bed (Electric or Manual Lift)				Windshield Fold Do			
							<input checked="" type="checkbox"/>
<b>OTHER PERFORMANCE:</b>				<b>TRANSAXLE:</b>			
Ash Tray				Limited Slip Differential			
Differential Gua						<input checked="" type="checkbox"/>	
Front Hydraulic Disc Brakes				<b>VEHICLE CAB:</b>			
Front Fascia & Brush Guard (Black)				Steel Cab (Tan):			
Glove Box Door (Locking) Driver Side							<input checked="" type="checkbox"/>
Glove Box Door (Locking) Passenger Side				Steel Cab (White):			
Horn							<input checked="" type="checkbox"/>
State of Charge Met		<input checked="" type="checkbox"/>		Steel Cab (Custom Color):			
International Tire							<input checked="" type="checkbox"/>
International Brushguard				Beacon, Amber (Cab Required)			
International Fender Flare							<input checked="" type="checkbox"/>
Canopy Handle				Defroster/Fan (Cab Required)			
							<input checked="" type="checkbox"/>
				Dome Light (Cab Required)			
							<input checked="" type="checkbox"/>
				Doors (Steel) Tan (Cab Required)			
							<input checked="" type="checkbox"/>
				Doors (Steel) White (Cab Required)			
							<input checked="" type="checkbox"/>
				Doors (Steel) Custom Color (Cab Required)			
							<input checked="" type="checkbox"/>
				Doors (Vinyl) Tan (Cab Required)			
							<input checked="" type="checkbox"/>
				Rear View Mirror (Cab Required)			
							<input checked="" type="checkbox"/>
				Strobe Light (Cab Required)			
							<input checked="" type="checkbox"/>
				Windshield Wiper (Cab Required)			
							<input checked="" type="checkbox"/>
				Work Light (Cab Required)			
							<input checked="" type="checkbox"/>