



**MODEL: HAULSTER**  
**TYPE: GASOLINE POWERED AUTOMATIC TRANSMISSION TRUCK**  
**MODEL YEAR: 2012**  
**Part No.: 84059**



### PRODUCT SPECIFICATION

#### CONFIGURATION HIGHLIGHTS

- Engine:** 26 hp (19.4 kW) rated, 4 cycle, 40.3 ci (660 cc) EFI, three cylinder, liquid-cooled by Suzuki
- **Valve Train:** 12 overhead valves, dual overhead cam, chain drive
  - **Lubrication:** Pressurized oil system, spin-on filter
  - **Air Cleaner:** Dry cartridge with evacuator valve
  - **Fuel System:** Electronic fuel injection
  - **Ignition:** Solid-state
- Electrical:** Starter, 60 Amp alternator, 12 Volt maintenance free battery (590 CCA, 85 minute reserve)  
**Ignition:** Electronic with cam trigger, electronic advance & RPM limiter  
**Drive Train:** 3 Speed automatic transmission. (3rd gear electronically disabled in Refresher application)  
**Brakes:** 4 Wheel hydraulic self-adjusting drum brakes [7.9 in (20 cm) dual-servo]. Mechanical hand brake  
**Rear axle:** Differential with hypoid gears  
**Capacity:** Seating for 2 persons

### PRODUCT OVERVIEW

#### Dimensions

Overall Length	136.0 in (345 cm)
Overall Width	53.0 in (135 cm)
Overall Height (No Canopy)	51.0 in (130 cm) (Top of steering wheel)
Overall Height (With ROPS)	74.0 in (188 cm)
Wheel Base	88.2 in (224 cm)
Front Wheel Track	42.0 in (107 cm)
Rear Wheel Track	44.0 in (112 cm)
Gnd Clearance @ Differential	5.0 in (13 cm)
Cargo Deck Size	47.4 in (120 cm) W x 72 in (183 cm) L
Cargo Deck Material	Diamond pattern steel

#### Vehicle Power

Power Source	4 cycle, 40.3 ci (660 cc) EFI, 3 cylinder
Valve Train	12 valve, dual OHV/OHC. Chain drive
Horsepower (kW)	26.0 hp (19.4 kW) @ 3600 rpm (governed)
Electrical System	12 Volt starter. 60 amp alternator
Battery (Qty, Type)	One 12 Volt maintenance free
Key or Pedal Start	Key start
Air Cleaner	Dry cartridge
Lubrication	Pressurized oil system
Oil Filter	Spin-on
Cooling System	Liquid cooled
Fuel Capacity	7.0 gallon (26.5 L) tank
Transmission	3 Speed automatic
Gear Selection	Neutral - Reverse - Park
Gear Shift location	Dash
Rear Axle Ratio	11.16:1

#### Performance

Seating Capacity	2 Persons
Curb Weight	1440 lb (650 kg)
Vehicle load capacity	2400 lb (1090 kg)
Outside Clearance Circle	20.2 ft (6.2 m)
Intersecting Aisle Clearance	N/A
Speed (Governed, Level Gnd)	20 mph ± 0.5 mph (32 kph ± 0.8 kph)
Towing Capacity	2400 lb (1090 kg)

#### Steering & Suspension

Steering	Automotive power
Front Suspension	Double A-arm independent w/spring over shocks
Rear Suspension	Multiple leaf springs
Rear Axle	Differential with hypoid gears
Service Brake	4 Wheel 7.9 (20 cm) hydraulic drum
Parking Brake	Mechanical hand brake
Front Tires	USA Trail 20.5 x 8 - 10 (Load range C)
Rear Tires	USA Trail 20.5 x 8 - 10 (Load range C)

#### Body & Chassis

Frame	Unitized welded steel channel. E-coat finish
Front Body & Finish	Polyethylene
Rear Body & Finish	Steel with rubber fender flairs
Storage	Hinged front cowl
Standard Color	Yellow



*Some items shown may be optional equipment*

